

Product Specification

DC Flexible LED Strip

2835 8LEDs/unit Series

2835 Top LED 12mm FPC 160LEDs/M

WW-FLS102T29XW160X-24(WCP)-30-XR-M-HE
&
WW-FLS102T29XW160X-24(WCP)-30-XR-M-HE-EP



HK Office :

Unit 1901, 19th Floor, NanYang Plaza, No. 57 Hung To Road
Kwun Tong, Kowloon, Hong Kong

China Factory :

Zhiyang Science and Technology Park, 10 Zhiyang Road, Zhangge,
Fucheng Street, Longhua District, Shenzhen, Guangdong, China

Tel : (852) 3152 3059 (10 lines)


Fax : (852) 3152 3039






Tel : (86) 755 8601 9190



Fax : (86) 755 8601 9197

<p>Product Features</p> <ul style="list-style-type: none"> • High quality FPC, authentic 3M tape; • Self-encapsulated design 2835 LED; • Light source lifetime:50K hours(L70); • Meet (EU)2019/2020 ErP regulations. • Min. Bending Diameter: Φ60mm • Max. length(M):3M 	
<p>Technology info</p> <ul style="list-style-type: none"> • Lighting Technology: LED • DLS or NDLS: NDLS • MLS or NMLS: NMLS 	<p>Certification Standards</p> <ul style="list-style-type: none"> • EN55015:2019 • EN61547:2009 • EN60598-1:2015 • EN60598-2-20:2015 • EN62493:2015 • EN62471:2008

Non-ErP Waterproof Type	 E 20	 S 54
	Naked Strip	Silicone Dropping
	5 Years Warranty	3 Years Warranty

ErP Waterproof Type	 E 20
	Naked Strip
	5 Years Warranty

WW-FLS102T29XW160X-24(WCP)-30-XR-M-HE

Parameters for non-Erp

IP Grade	Model NO.	CRI (Ra)	Rf	Rg	Typical Power (W/M)	Max. Power (W/M)	Color	LED Color Temp.(K) Wavelength(nm)*	3SDCM LED Color Temp.(K) Wavelength(nm)**	Typ. Luminous Flux LM/M(39.37in)	Rated voltage
B 20	WW-FLS102T29XW160B-24(WCP)-30-HR-M-HE	80	82	96	23.80	26.18	Warm White	2300-2600K	/	3270	DC 24V
							Warm White	2600-2900K	/	3380	
							Warm White	2900-3200K	/	3510	
							Natural White	3700-4250K	/	3700	
							Standard White	5700-6500K	/	3680	
	WW-FLS102T29XW160B-24(WCP)-30-UR-M-HE	90	90	100	23.80	26.18	Warm White	2300-2600K	/	2560	DC 24V
							Warm White	2600-2900K	/	2860	
							Warm White	2900-3200K	/	2930	
							Natural White	3700-4250K	/	3060	
							Standard White	5700-6500K	/	3110	
S 54	WW-FLS102T29XW160S-24(WCP)-30-HR-M-HE	80	82	96	23.80	26.18	Warm White	2300-2600K	/	3075	DC 24V
							Warm White	2600-2900K	/	3075	
							Warm White	2900-3200K	/	3195	
							Natural White	3700-4250K	/	3110	
							Standard White	5700-6500K	/	2910	
	WW-FLS102T29XW160S-24(WCP)-30-UR-M-HE	90	90	100	23.80	26.18	Warm White	2300-2600K	/	2485	DC 24V
							Warm White	2600-2900K	/	2660	
							Warm White	2900-3200K	/	2665	
							Natural White	3700-4250K	/	2755	
							Standard White	5700-6500K	/	2580	

Remarks:

- *The above color temperature is the color temperature of LED source.
- **Indicates SDCM<3 model is available, part number will add the suffix "-3S".
- The typ. Luminous flux tolerance range is ±15% (subject to the manufacturer's instrument test).

Test condition of above technical data:

- Surrounding temperature: 26°C.
- Test while turning on.

WW-FLS102T29XW160B-24(WCP)-30-XR-M-HE-EP

Parameters for Erp

IP Grade	Model NO.	CRI (Ra)	Rf	Rg	Typical Power (W/M)	Max. Power (W/M)	Color	LED Color Temp.(K) Wavelength(nm)*	Luminous Flux LM/M(39.37')	Lumen/watt	Energy Efficiency class	Rated voltage
B 20	WW-FLS102T29XW160B-24(WCP)-30-HR-M-HE-EP	80	82	96	21.82	24.00	Warm White	2500K	2997	137	D	DC 24V
							Warm White	2700K	3072	141	D	
							Warm White	3000K	3212	147	D	
							Natural White	4000K	3428	157	D	
							Standard White	6000K	3417	157	D	
	WW-FLS102T29XW160B-24(WCP)-30-UR-M-HE-EP	90	90	100	21.82	24.00	Warm White	2500K	2328	107	F	DC 24V
							Warm White	2700K	2587	119	E	
							Warm White	3000K	2684	123	E	
							Natural White	4000K	2770	127	E	
							Standard White	6000K	2867	131	E	

Remarks:

- *The above color temperature is the color temperature of LED source.
- While SDCM<3 model is available, part number will add the suffix "-3S".




Test condition of above technical data:

- Surrounding temperature: 26 °C.
- Test after 15 mins turned on.


ErP Note:

- According to the new ErP 2019/2020 regulation for each 0.5m or nearest 0.5m strip, the following requirements must be met:
- Measured power ≤ Pon +5% ;
- Measured lumen ≥Useful luminous flux -10%;
- Measured CRI ≥ Declared CRI-2
- The above technical data, including typical power are based on the test of 0.5m.

Optical Test Diagram



Dimension Drawing




IP Grade	A	B	C	D	E	F	G	H	I
	Cable Length	cable diameter	Strip length	Strip width	Strip thickness	Front cap length	End cap length	Cap width	Cap thickness
E 20	300±10mm	Φ6.0±0.2mm	3000±50mm	12±0.5mm	1.2±0.5mm	/	/	/	/
	11.81±0.39in	0.236±0.008in	118.11±1.97in	0.473±0.02in	0.047±0.02in	/	/	/	/
S 54	300±10mm	Φ6.0±0.2mm	3000±50mm	12±0.5mm	2.8±0.5mm	/	/	/	/
	11.81±0.39in	0.236±0.008in	118.11±1.97in	0.473±0.02in	0.11±0.02in	/	/	/	/



Remarks:

- If you need further information, please contact our sales manager.


Circuit Diagram



Optional Accessories

IP Grade	Category	Description	Picture	Part No.	Application
B 20	Strip to wire Connector	2PIN Strip to wire Connector		WW-F2B-PWP2O-12-0-18	≤240LEDs/M
	Strip to strip Connector	2PIN Strip to strip Connector		WW-F2B-POP2O-12-0-0	≤240LEDs/M
S 54	/	/	/	/	/
	/	/	/	/	/

Packaging Diagram













Packaging information

















IP Grade	Bag size	Inner carton		Outer carton		N.W	G.W	Outer carton volume
		Size	Reel/ctn	Size	Reel/ctn			
B 20	250*270*0.14mm	/	/	440*400 *260mm	50	3.3KG ±10%	8.19KG ±10%	0.04576 m ³
	9.84*10.63*0.0056 in	/	/	17.32*15.75 *10.24in	50	7.28Lbs ±10%	18.06Lbs ±10%	1.616 ft ³
S 54	250*270*0.14mm	/	/	440*400 *260mm	40	5.178KG ±10%	10KG ±10%	0.04576 m ³
	9.84*10.63*0.0056 in	/	/	17.32*15.75 *10.24in	40	11.415Lbs ±10%	22Lbs ±10%	1.616 ft ³

Remarks :

- Please contact our sales manager for customized package (color box, blister etc.)

 **Cautions**

IP20	IP54	IP65	IP67	IP68
				
Do not press the surface of LED	Pay attention to high temperature environment	Do not use in strong water waves environment	Resist strong water waves impact	Can apply to underwater do not deeper than 1m
				
Pay attention to damp-proof and dustproof	Do not apply to rainy environment	Can be applied to rainy environment	Do not apply to underwater environment for a long time	No direct sunlight

							
Do not tie a knot	Do not winding	Do not twist	Do not cut when it is working	Recommended the continuous working time do not exceed 12 hours daily	-20°C~+45°C (-4°F~+113°F)	0°C~+60°C (32°F~+140°F)	Operated by professionals
							
Pay attention to the application environment	IP Level will change after cutting	Do not pull and crash	Connected to power supply every 5 meters	Power supply must be connected to ground(GND)	The minimum bending diameter > 60mm	Power supply retain > 20%	Note the positive and negative poles



For cutting LED strip operation, it is necessary to use the standard accessories provided by Dilux (e.g. DC wire, end-cap, front-cap, adhesive, etc.), and according to the correct cutting and connecting method for the installation.



For avoiding LED get vulcanized, LED strip should be installed in the environment where does not has oil and corrosive substances. Such as these substances which contain Sulphur, Bromine, Iodine and Chlorine. Some other chemical elements which will cause Aromatic hydrocarbons releasing(such as: methylbenzene, xylene, methyl acetoacetate Ethyl acetate etc.),The environment in which includes strong acid and strong base.



During the warranty period, only defective products are acceptable to be replaced by the factory. Factory is not responsible for other expenses because of replacement, such as transportation fee, installation fee, etc..

**** If you do not follow the above "Cautions" to operate and result in damaging the product, the factory will not accept maintenance and return.**
****The right of final interpretation is owned by Dilux.**