

Product Specification

DC Flexible LED Strip

Ultra Long 2835 Series

2835 Top LED 10mm FPC 70LEDs/M

WW-FLS102T23XW070X-24(WCP)-1500-HR-ME-TR-LD
&
WW-FLS102T23XW070X-24(WCP)-1500-HR-ME-TR-EP-LD



HK Office :

Unit 1901, 19th Floor, NanYang Plaza, No. 57 Hung To Road
Kwun Tong, Kowloon, Hong Kong

China Factory :

Zhiyang Science and Technology Park, 10 Zhiyang Road, Zhangge,
Fucheng Street, Longhua District, Shenzhen, Guangdong, China

Tel : (852) 3152 3059 (10 lines)


Fax : (852) 3152 3039



Tel : (86) 755 8601 9190



Fax : (86) 755 8601 9197

Product Features • High quality FPC, authentic 3M tape; • Self-encapsulated design 2835 LED; • Light source lifetime:50K hours(L70); • Meet (EU)2019/2020 ErP regulations. • Min. Bending Diameter: Φ60mm • Max. length(M): 15M	
Technology info • Lighting Technology: LED • DLS or NDLS: NDLS • MLS or NMLS: NMLS	Certification Standards • EN55015:2013+A1 • EN61547:2009 • EN60598-1:2015 • EN60598-2-20:2015 • EN62493:2015 • EN62471:2008

Non-ErP Waterproof Type		
	B 20	R 67
	Naked Strip	Silicone Extrusion
	3 Years Warranty	3 Years Warranty

ErP Waterproof Type		
	B 20	R 67
	Naked Strip	Silicone Extrusion
	3 Years Warranty	3 Years Warranty

WW-FLS102T23XW070X-24(WCP)-1500-HR-ME-TR-LD

Parameters for non-ErP

IP Grade	Model NO.	CRI (Ra)	Rf	Rg	Typical Power (W/M)	Max. Power (W/M)	Color	LED Color Temp.(K) Wavelength(nm)*	3SDCM LED Color Temp.(K) Wavelength(nm)**	Typ. Luminous Flux LM/M(39.37in)	Rated voltage
E 20	WW-FLS102T23WW070B-24(WCP)-1500-HR-ME-TR-LD	80	82	96	5.00	5.50	Warm White	2600-2900K	2650-2770K	580	DC 24V
	WW-FLS102T23WW070B-24(WCP)-1500-HR-ME-TR-LD						Warm White	2900-3200K	2960-3110K	614	
	WW-FLS102T23NW070B-24(WCP)-1500-HR-ME-TR-LD						Natural White	3700-4250K	3840-4080K	648	
	WW-FLS102T23SW070B-24(WCP)-1500-HR-ME-TR-LD						Standard White	5700-6500K	5800-6250K	636	
R 67	WW-FLS102T23WW070R-24(WCP)-1500-HR-ME-TR-LD	80	82	96	5.00	5.50	Warm White	2600-2900K	2650-2770K	560	DC 24V
	WW-FLS102T23WW070R-24(WCP)-1500-HR-ME-TR-LD						Warm White	2900-3200K	2960-3110K	590	
	WW-FLS102T23NW070R-24(WCP)-1500-HR-ME-TR-LD						Natural White	3700-4250K	3840-4080K	625	
	WW-FLS102T23SW070R-24(WCP)-1500-HR-ME-TR-LD						Standard White	5700-6500K	5800-6250K	568	

Remarks:

- * The above color temperature is the color temperature of LED source.
- ** Indicates SDCM<3 model is available, part number will add the suffix "-3S".
- The typ. Luminous flux tolerance range is $\pm 10\%$ (subject to the manufacturer's instrument test).

Test condition of above technical data:

- Surrounding temperature: 26°C.
- Test while turning on.
- The above technical data, including typical power are based on the test of 0.5m.

WW-FLS102T23XW070X-24(WCP)-1500-HR-ME-TR-EP-LD

Parameters for ErP

IP Grade	Model NO.	CRI (Ra)	Rf	Rg	Typical Power (W/M)	Max. Power (W/M)	Color	LED Color Temp.(K) Wavelength(nm)*	Luminous Flux LM/M(39.37')	Lumen/watt	Energy Efficiency class	Rated voltage
E 20	WW-FLS102T23WW070B-24(WCP)-1500-HR-ME-TR-EP-LD	80	82	96	4.80	5.28	Warm White	2700	510	106	F	DC 24V
	WW-FLS102T23WW070B-24(WCP)-1500-HR-ME-TR-EP-LD						Warm White	3000	540	113	E	
	WW-FLS102T23NW070B-24(WCP)-1500-HR-ME-TR-EP-LD						Natural White	4000	570	119	E	
	WW-FLS102T23SW070B-24(WCP)-1500-HR-ME-TR-EP-LD						Standard White	6000	560	117	E	
R 67	WW-FLS102T23WW070R-24(WCP)-1500-HR-ME-TR-EP-LD	80	82	96	4.80	5.28	Warm White	2700	490	102	F	DC 24V
	WW-FLS102T23WW070R-24(WCP)-1500-HR-ME-TR-EP-LD						Warm White	3000	520	108	F	
	WW-FLS102T23NW070R-24(WCP)-1500-HR-ME-TR-EP-LD						Natural White	4000	550	115	E	
	WW-FLS102T23SW070R-24(WCP)-1500-HR-ME-TR-EP-LD						Standard White	6000	500	104	F	

Remarks:

- *The above color temperature is the color temperature of LED source.


Test condition of above technical data:

- Surrounding temperature: 26 °C.
- Test after 10 mins turned on.


ErP Note:

- According to the new ErP 2019/2020 regulation for each 0.5m or nearest 0.5m strip, the following requirements must be met:
- Measured power $\leq$ Pon +5% ;
- Measured lumen $\geq$ Useful luminous flux -10%;
- Measured CRI $\geq$ Declared CRI-2
- The above technical data, including typical power are based on the test of 0.5m.

Optical Test Diagram



Dimension Drawing




IP Grade	A Cable Length	B cable diameter	C Strip length	D Strip width	E Strip thickness	F Cap thickness	G End cap length	H Cap width
E20	300±10mm	Φ1.8±0.2mm	15,000±50mm	10±0.5mm	1.2±0.2mm	/	/	/
	11.81±0.39in	0.16±0.01in	196.85±1.97in	0.394±0.02in	0.047±0.02in	/	/	/
R67	300±10mm	Φ6.0±0.2mm	15,020±50mm	12±0.5mm	4.5±0.5mm	7.0±1mm	11±0.5mm	14±0.5mm
	11.81±0.39in	0.236±0.008in	197.64±1.97in	0.472±0.02in	0.20±0.02in	0.28±0.02in	0.43±0.02in	0.55±0.02in

Remarks:

- If you need further information, please contact our sales manager.

Circuit Diagram




Standard Accessories

IP Grade	Category	Description	Picture	Part No.	Application
B 20	/	/	/	/	/
	/	/	/	/	/
R 67	Connection Accessories	Front cap+End cap+Cable		WW-FLS102F-CW(10mm)	10mm Type R Waterproof strip
	Installation Accessories	Installation Buckle+Screws		WW-FLS102JJA-MC	

Optional Accessories

IP Grade	Category	Description	Picture	Part No.	Application
B 20	Strip to strip Connector	2PIN Strip to strip Connector		WW-FLS102BPWP-10(10MM)	≤240LEDs/M
	Strip to strip Connector	2PIN Strip to strip Connector		WW-FLS102BPOP-10(10MM)	≤240LEDs/M

Packaging Diagram



Packaging Diagram

IP Grade	Bag size	Inner carton		Outer carton		N.W	G.W	Outer carton volume
		Size	Reel/ctn	Size	Reel/ctn			
B 20	250*270*0.14mm	/	/	440*400*260mm	50	12.4KG ±10%	18.5 KG ±10%	0.0458m³
	9.84*10.63*0.0056 in	/	/	17.32*15.75 *10.24 in	50	27.34Lbs ±10%	40.79 Lbs ±10%	1.616 ft³
R 67	470*440*0.14mm	/	/	440*400*260mm	11	8.5 KG ±10%	13.59KG ±10%	0.0458m³
	18.5*17.32*0.0056 in	/	/	17.32*15.75 *10.24 in	11	18.74 Lbs ±10%	29.96Lbs ±10%	1.616 ft³

Remarks :

- Please contact our sales manager for customized package (color box, blister etc.)

 Cautions

IP20	IP54	IP65	IP67	IP68
				
Do not press the surface of LED	Pay attention to high temperature environment	Do not use in strong water waves environment	Resist strong water waves impact	Can apply to underwater do not deeper than 1m
				
Pay attention to damp-proof and dustproof	Do not apply to rainy environment	Can be applied to rainy environment	Do not apply to underwater environment for a long time	No direct sunlight

							
Do not tie a knot	Do not winding	Do not twist	Do not cut when it is working	Recommended the continuous working time do not exceed 12 hours daily	-20°C~+45°C (-4°F~+113°F)	0°C~+60°C (32°F~+140°F)	Operated by professionals
							
Pay attention to the application environment	IP Level will change after cutting	Do not pull and crash	Connected to power supply every 5 meters	Power supply must be connected to ground(GND)	The minimum bending diameter > 60mm	Power supply retain > 20%	Note the positive and negative poles

 For cutting LED strip operation, it is necessary to use the standard accessories provided by Dilux (e.g. DC wire, end-cap, front-cap, adhesive, etc.), and according to the correct cutting and connecting method for the installation.

 For avoiding LED get vulcanized, LED strip should be installed in the environment where does not has oil and corrosive substances. Such as these substances which contain Sulphur, Bromine, Iodine and Chlorine. Some other chemical elements which will cause Aromatic hydrocarbons releasing(such as: methylbenzene, xylene, methyl acetoacetate Ethyl acetate etc.).The environment in which includes strong acid and strong base.

 During the warranty period, only defective products are acceptable to be replaced by the factory. Factory is not responsible for other expenses because of replacement, such as transportation fee, installation fee, etc..

**** If you do not follow the above "Cautions" to operate and result in damaging the product, the factory will not accept maintenance and return.**

****The right of final interpretation is owned by Dilux.**