

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
 Humidity:65.0%
 Test Distance:4.880m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	264.3	261.3	258.4	256.4	270.0	264.7	259.5	251.0	0- 10	24.97	24.97	2.31,2.31
20	252.0	249.2	247.0	250.1	263.0	256.4	249.0	238.7	10- 20	72.28	97.25	8.99,8.99
30	235.6	231.2	228.6	238.3	251.0	242.0	231.1	220.8	20- 30	112.0	209.3	19.3,19.3
40	216.5	208.6	202.8	221.4	235.8	222.4	206.0	198.3	30- 40	140.6	349.9	32.3,32.3
50	194.6	182.3	169.7	200.5	217.2	199.0	173.4	172.2	40- 50	155.4	505.3	46.7,46.7
60	172.8	152.7	129.6	175.6	196.6	172.0	133.6	143.7	50- 60	155.6	660.9	61.1,61.1
70	152.7	124.7	83.44	149.9	175.1	144.1	88.10	115.6	60- 70	142.9	803.8	74.3,74.3
80	130.7	99.66	36.99	124.9	152.9	117.8	41.46	91.81	70- 80	121.3	925.1	85.5,85.5
90	89.71	61.25	4.066	93.21	120.1	84.85	8.728	52.51	80- 90	91.59	1017	94,94
100	8.738	3.199	1.359	28.32	62.95	20.05	1.494	8.239	90-100	43.31	1060	98,98
110	2.304	2.208	1.556	3.197	2.493	2.479	1.615	3.764	100-110	8.379	1068	98.8,98.8
120	2.399	2.189	1.853	1.895	2.159	1.958	2.425	4.226	110-120	2.916	1071	99,99
130	2.504	2.383	2.135	2.162	2.336	2.211	2.555	5.233	120-130	2.582	1074	99.3,99.3
140	2.632	2.566	2.391	2.359	2.507	2.424	2.708	6.301	130-140	2.487	1076	99.5,99.5
150	2.784	2.755	2.701	2.593	2.682	2.642	2.858	7.402	140-150	2.184	1079	99.7,99.7
160	2.959	2.937	2.915	4.088	2.899	2.855	2.997	8.074	150-160	1.747	1080	99.9,99.9
170	3.127	3.103	3.094	6.598	3.104	3.053	3.101	8.244	160-170	1.155	1081	100,100
180	3.231	3.195	3.280	8.256	3.230	3.193	3.180	8.013	170-180	0.4136	1082	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2022-03-19

□ Range: 0 - 180DEG
□ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
Humidity:65.0%
Test Distance:4.880m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20g
SPEC.: COB LED	DIM.: 500*8*1.9mm	SERIAL No.: 20220319009
MFR.: EVERFINE	SUR.: 500*8*1.9mm	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	158848	25106
80	94077	26627
75	69241	28815
70	55805	30496
65	48070	31686
60	43189	32396
55	39971	32803
50	37843	32996
45	36391	33087


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2022-03-19

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.444
Humidity: 65.0%
Test Distance: 4.880m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20g
SPEC.: COB LED	DIM.: 500*8*1.9mm	SERIAL No.: 20220319009
MFR.: EVERFINE	SUR.: 500*8*1.9mm	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2022-03-19

□ Range: 0 - 180DEG
 □ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
 Humidity:65.0%
 Test Distance:4.880m [K=1.0000]
 Remarks:

WEC AND CCEC

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20g
SPEC.: COB LED	DIM.: 500*8*1.9mm	SERIAL No.: 20220319009
MFR.: EVERFINE	SUR.: 500*8*1.9mm	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0	
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
□fc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.405	.230	.073	.396	.226	.072	.379	.217	.069	.363	.209	.067	.349	.202	.065		
2.0	.349	.191	.059	.341	.188	.058	.326	.181	.056	.311	.175	.055	.298	.169	.053		
3.0	.309	.164	.049	.302	.162	.049	.288	.156	.047	.275	.151	.046	.263	.146	.045		
4.0	.277	.144	.042	.271	.142	.042	.258	.137	.041	.247	.133	.040	.236	.128	.039		
5.0	.251	.128	.037	.245	.126	.037	.234	.122	.036	.224	.118	.035	.214	.115	.034		
6.0	.230	.115	.033	.224	.113	.033	.214	.110	.032	.205	.107	.031	.196	.103	.031		
7.0	.211	.105	.030	.207	.103	.029	.198	.100	.029	.189	.097	.028	.181	.094	.028		
8.0	.196	.096	.027	.192	.094	.027	.183	.092	.026	.176	.089	.026	.169	.087	.025		
9.0	.182	.088	.025	.178	.087	.024	.171	.085	.024	.164	.082	.024	.157	.080	.023		
10.0	.170	.082	.023	.167	.081	.022	.160	.078	.022	.154	.076	.022	.148	.074	.021		

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.236	.236	.236	.202	.202	.202	.138	.138	.138	.079	.079	.079	.025	.025	.025	
1.0	.233	.202	.173	.200	.173	.149	.136	.119	.103	.079	.069	.060	.025	.022	.019	
2.0	.226	.178	.138	.194	.153	.119	.133	.106	.083	.077	.062	.049	.025	.020	.016	
3.0	.219	.161	.116	.188	.139	.100	.129	.097	.070	.074	.056	.041	.024	.018	.014	
4.0	.211	.149	.101	.181	.128	.088	.124	.090	.062	.072	.052	.037	.023	.017	.012	
5.0	.203	.139	.091	.174	.120	.079	.120	.084	.056	.069	.049	.033	.022	.016	.011	
6.0	.195	.130	.084	.168	.113	.073	.116	.079	.052	.067	.047	.031	.022	.015	.010	
7.0	.188	.124	.079	.161	.107	.069	.112	.075	.049	.065	.044	.029	.021	.015	.010	
8.0	.181	.118	.075	.156	.102	.065	.108	.072	.046	.063	.042	.028	.020	.014	.009	
9.0	.174	.113	.072	.150	.098	.063	.104	.069	.045	.061	.041	.027	.020	.013	.009	
10.0	.168	.109	.069	.145	.094	.061	.101	.066	.043	.059	.039	.026	.019	.013	.009	

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2022-03-19

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
Humidity:65.0%
Test Distance:4.880m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

NAME: LED Strip					TYPE: Indoor lighting			WEIGHT:20g			
SPEC.: COB LED					DIM.: 500*8*1.9mm			SERIAL No.: 20220319009			
MFR.: EVERFINE					SUR.: 500*8*1.9mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	25.1	26.7	25.5	27.0	27.4	23.9	25.5	24.3	25.8	26.1
	3H	27.8	29.3	28.2	29.6	30.0	25.6	27.0	26.0	27.4	27.8
	4H	29.3	30.7	29.7	31.1	31.5	26.3	27.7	26.7	28.0	28.4
	6H	31.0	32.3	31.4	32.7	33.1	26.8	28.1	27.2	28.5	28.9
	8H	31.9	33.1	32.3	33.5	34.0	27.0	28.3	27.4	28.7	29.1
	12H	32.8	34.0	33.2	34.4	34.9	27.1	28.4	27.6	28.8	29.2
4H	2H	25.8	27.2	26.2	27.6	28.0	24.9	26.3	25.3	26.7	27.0
	3H	28.7	30.0	29.2	30.4	30.8	26.8	28.1	27.3	28.5	28.9
	4H	30.4	31.6	30.9	32.0	32.5	27.7	28.8	28.2	29.3	29.7
	6H	32.3	33.3	32.8	33.8	34.3	28.4	29.4	28.9	29.9	30.4
	8H	33.3	34.3	33.8	34.8	35.3	28.7	29.6	29.2	30.1	30.7
	12H	34.4	35.3	34.9	35.8	36.3	28.9	29.8	29.4	30.3	30.8
8H	4H	30.8	31.8	31.4	32.3	32.8	28.7	29.6	29.2	30.1	30.6
	6H	33.0	33.9	33.6	34.4	34.9	29.7	30.6	30.3	31.1	31.7
	8H	34.2	35.0	34.8	35.5	36.1	30.2	31.0	30.8	31.5	32.1
	12H	35.5	36.2	36.1	36.8	37.4	30.6	31.3	31.2	31.8	32.4
12H	4H	30.9	31.8	31.4	32.3	32.8	29.0	29.9	29.5	30.4	30.9
	6H	33.2	33.9	33.7	34.5	35.0	30.3	31.0	30.8	31.6	32.1
	8H	34.5	35.1	35.1	35.7	36.3	30.9	31.6	31.5	32.1	32.8
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.2					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.3					

CIE Pub.117, 1082 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.3)
Area: 0.008 m2


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2022-03-19

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
Humidity:65.0%
Test Distance:4.880m [K=1.0000]
Remarks:

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
 Humidity:65.0%
 Test Distance:4.880m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20g
SPEC.: COB LED	DIM.: 500*8*1.9mm	SERIAL No.: 20220319009
MFR.: EVERFINE	SUR.: 500*8*1.9mm	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2022-03-19

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.444
 Humidity: 65.0%
 Test Distance: 4.880m [K=1.0000]
 Remarks:

AAI Figure

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20g
SPEC.: COB LED	DIM.: 500*8*1.9mm	SERIAL No.: 20220319009
MFR.: EVERFINE	SUR.: 500*8*1.9mm	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2022-03-19

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
 Humidity:65.0%
 Test Distance:4.880m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20g
SPEC.: COB LED	DIM.: 500*8*1.9mm	SERIAL No.: 20220319009
MFR.: EVERFINE	SUR.: 500*8*1.9mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2022-03-19

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.444
 Humidity: 65.0%
 Test Distance: 4.880m [K=1.0000]
 Remarks:

LED Avg.L Report

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20g
SPEC.: COB LED	DIM.: 500*8*1.9mm	SERIAL No.: 20220319009
MFR.: EVERFINE	SUR.: 500*8*1.9mm	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	51537
L_0~180 (75) av	74221
L_0~180 (85) av	179952
L_90~270 (65) av	32320
L_90~270 (75) av	29946
L_90~270 (85) av	28094
L_45 (65) av	43494
L_45 (75) av	58318
L_45 (85) av	135527

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2022-03-19

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.444
 Humidity: 65.0%
 Test Distance: 4.880m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2022-03-19

☐ Range: 0 - 180DEG
☐ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.444
 Humidity: 65.0%
 Test Distance: 4.880m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20g
SPEC.: COB LED	DIM.: 500*8*1.9mm	SERIAL No.: 20220319009
MFR.: EVERFINE	SUR.: 500*8*1.9mm	Shielding Angle:

Table--1

UNIT: cd

C (DEG) □ (DEG)	0	15	30	45	60	75	90	105	120	135	150	165	180	195	210	225	240	255	270
0	271	270	268	266	265	264	263	261	255	257	260	262	271	270	268	266	265	264	263
5	268	267	266	265	263	263	261	260	255	257	261	263	271	270	268	266	265	263	262
10	264	264	262	261	260	260	258	257	254	256	260	262	270	269	267	265	263	261	259
15	259	258	257	256	255	255	254	253	251	254	258	260	267	266	264	261	259	257	255
20	252	252	250	249	248	248	247	247	247	250	254	257	263	261	260	256	254	251	249
25	244	244	242	241	239	240	239	239	241	245	249	252	258	256	254	250	247	243	241
30	236	235	233	231	229	229	229	230	233	238	243	247	251	249	246	242	238	234	231
35	226	226	223	220	217	217	217	219	225	230	236	240	244	242	238	233	227	222	219
40	217	216	213	209	204	203	203	206	214	221	228	233	236	234	229	222	215	209	206
45	206	205	201	196	190	188	187	191	202	211	219	225	227	225	219	211	202	194	191
50	195	193	189	182	175	171	170	175	189	200	209	216	217	215	209	199	188	178	173
55	183	181	176	168	158	152	151	157	175	188	199	207	207	204	197	186	172	160	154
60	173	170	163	153	141	132	130	138	160	176	189	198	197	194	185	172	156	140	134
65	163	159	151	138	123	111	107	117	145	163	178	187	186	183	173	158	139	120	111
70	153	149	140	125	106	90.1	83.4	97.3	129	150	166	177	175	172	161	144	122	98.6	88.1
75	143	139	129	112	89.9	69.2	59.7	77.3	114	137	155	166	164	160	149	131	106	78.2	64.3
80	131	127	117	99.7	75.6	49.8	37.0	58.2	100.0	125	143	155	153	149	137	118	90.6	59.2	41.5
85	111	108	97.8	82.5	60.3	34.2	17.5	41.9	86.2	113	131	143	140	136	124	105	76.5	43.1	21.7
90	89.7	86.7	76.5	61.3	40.6	18.9	4.07	26.3	68.3	93.2	111	123	120	116	104	84.9	58.5	27.9	8.73
95	40.6	38.3	29.6	17.6	6.32	2.94	1.52	5.33	44.0	69.9	88.5	100	95.8	91.9	80.1	61.2	34.5	8.01	2.64
100	8.74	7.94	5.37	3.20	2.58	1.91	1.36	2.65	10.1	28.3	50.9	66.9	63.0	56.9	42.7	20.1	6.18	5.84	1.49
105	2.59	2.63	2.55	2.40	2.21	1.67	1.41	1.92	2.59	8.51	16.7	26.5	16.6	12.3	5.82	4.30	4.63	4.89	1.53
110	2.30	2.30	2.27	2.21	1.93	1.72	1.56	1.78	1.69	3.20	7.84	16.3	2.49	2.28	2.10	2.48	3.65	2.27	1.61
115	2.32	2.33	2.27	2.20	1.93	1.80	1.70	1.73	1.72	1.95	3.36	8.43	2.15	2.09	2.00	1.85	1.87	1.70	1.85
120	2.40	2.40	2.34	2.19	2.04	1.93	1.85	1.84	1.85	1.89	2.23	3.61	2.16	2.11	2.06	1.96	1.89	1.84	2.43
125	2.45	2.44	2.39	2.29	2.16	2.06	2.00	1.98	1.98	2.02	2.13	2.39	2.25	2.22	2.18	2.09	2.03	1.99	2.49
130	2.50	2.49	2.45	2.38	2.27	2.19	2.14	2.12	2.19	2.16	2.23	2.21	2.34	2.31	2.28	2.21	2.16	2.14	2.56
135	2.57	2.58	2.53	2.48	2.38	2.31	2.26	2.25	2.63	2.27	2.34	2.34	2.42	2.39	2.38	2.32	2.29	2.27	2.62
140	2.63	2.64	2.61	2.57	2.48	2.43	2.39	2.37	3.20	2.36	2.44	2.45	2.51	2.48	2.48	2.42	2.41	2.40	2.71
145	2.70	2.72	2.69	2.66	2.59	2.55	2.51	2.50	3.98	2.47	2.52	2.56	2.59	2.57	2.57	2.53	2.53	2.53	2.79
150	2.78	2.81	2.78	2.75	2.70	2.67	2.70	2.64	5.13	2.59	2.63	2.66	2.68	2.67	2.67	2.64	2.65	2.65	2.86
155	2.87	2.89	2.86	2.84	2.80	2.79	2.81	2.79	6.10	2.97	2.78	2.77	2.79	2.76	2.78	2.75	2.76	2.77	2.93
160	2.96	2.97	2.95	2.94	2.90	2.90	2.91	2.89	6.99	4.09	2.90	2.88	2.90	2.87	2.88	2.86	2.87	2.87	3.00
165	3.05	3.05	3.02	3.03	2.99	2.99	3.01	3.03	7.87	5.39	3.02	3.00	3.01	2.96	2.98	2.96	2.98	2.97	3.05
170	3.13	3.13	3.10	3.10	3.08	3.08	3.09	3.24	8.67	6.60	4.11	3.17	3.10	3.06	3.07	3.05	3.07	3.06	3.10
175	3.19	3.18	3.16	3.16	3.14	3.15	3.18	3.56	9.19	7.87	5.70	3.29	3.18	3.14	3.16	3.13	3.15	3.13	3.15
180	3.23	3.21	3.19	3.19	3.19	3.19	3.28	3.75	9.26	8.26	6.59	4.55	3.23	3.20	3.20	3.19	3.19	3.18	3.18

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2022-03-19

□ Range: 0 - 180DEG
□ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
Humidity:65.0%
Test Distance:4.880m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: LED Strip	TYPE: Indoor lighting	WEIGHT: 20g
SPEC.: COB LED	DIM.: 500*8*1.9mm	SERIAL No.: 20220319009
MFR.: EVERFINE	SUR.: 500*8*1.9mm	Shielding Angle:

Table--2

UNIT: cd

C (DEG) □ (DEG)	285	300	315	330	345														
0	261	255	257	260	262														
5	260	253	255	257	259														
10	257	250	251	253	255														
15	253	244	246	248	249														
20	247	237	239	241	242														
25	239	229	230	233	234														
30	229	219	221	224	224														
35	217	207	210	214	215														
40	204	194	198	203	204														
45	189	180	186	191	193														
50	173	165	172	179	181														
55	155	149	158	166	169														
60	135	132	144	154	158														
65	115	114	129	141	148														
70	94.5	97.3	116	130	139														
75	74.4	81.1	103	120	133														
80	55.2	67.0	91.8	111	116														
85	39.9	56.8	78.4	90.0	91.7														
90	24.9	34.3	52.5	66.6	63.1														
95	10.5	11.4	22.7	25.5	28.8														
100	9.60	3.17	8.24	12.9	14.4														
105	8.04	3.03	3.70	5.28	6.69														
110	7.60	3.36	3.76	3.91	3.46														
115	7.18	3.72	4.02	4.07	3.65														
120	6.94	4.69	4.23	4.32	3.88														
125	6.76	5.76	4.72	4.53	4.14														
130	6.58	9.81	5.23	4.91	4.44														
135	6.43	9.24	5.76	5.32	4.78														
140	6.26	8.71	6.30	5.74	5.18														
145	6.06	8.26	6.91	6.20	5.47														
150	5.86	7.90	7.40	6.66	5.77														
155	5.64	7.50	7.78	7.02	6.02														
160	5.43	6.98	8.07	7.40	6.21														
165	5.24	6.38	8.21	7.63	6.25														
170	5.09	5.90	8.24	7.54	6.13														
175	4.88	5.59	8.18	7.27	5.25														
180	4.58	4.94	8.01	6.76	4.29														

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2022-03-19

□ Range: 0 - 180DEG
□ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
Humidity:65.0%
Test Distance:4.880m [K=1.0000]
Remarks: