

# Product Specification

## SMD LV Strip POP 2835 24V 120 LEDs/M Tunable White

WW-FLS102T23W-S120X-24(WCP)-HR-LD  
&  
WW-FLS102T23W-S120X-24(WCP)-HR-EP-LD

Apply to ERP Regulation (EU) 2019/2020



HK Office :

Unit 1901, 19th Floor, NanYang Plaza, No. 57 Hung To Road  
Kwun Tong, Kowloon, Hong Kong

China Factory :

Zhiyang Science and Technology Park, 10 Zhiyang Road, Zhangge,  
Fucheng Street, Longhua District, Shenzhen, Guangdong, China

Tel : (852) 3152 3059 (10 lines)


Fax : (852) 3152 3039









Tel : (86) 755 8601 9190



Fax : (86) 755 8601 9197

<p><b>Product Features</b></p> <ul style="list-style-type: none"> <li>• High quality FPC, authentic 3M tape;</li> <li>• Self-encapsulated design 2835 LED;</li> <li>• Light source lifetime:50K hours(L70);</li> <li>• Meet (EU)2019/2020 ErP regulations.</li> <li>• Min. Bending Diameter: Φ60mm</li> <li>• Max. length(M): 5M</li> </ul>	
<p><b>Technology info</b></p> <ul style="list-style-type: none"> <li>• Lighting Technology: LED</li> <li>• DLS or NDLS: NDLS</li> <li>• MLS or NMLS: NMLS</li> </ul>	<p><b>Certification Standards</b></p> <ul style="list-style-type: none"> <li>• EN55015:2019</li> <li>• EN61547:2009</li> <li>• EN60598-1:2015</li> <li>• EN60598-2-20:2015</li> <li>• EN62493:2015</li> <li>• EN62471:2008</li> </ul>

<b>Non-ErP Waterproof Type</b>	 <b>B 20</b>	 <b>F 65</b>	 <b>R 67</b>
	Naked Strip	Silicone Tube	Silicone Extrusion
	3 Years Warranty	3 Years Warranty	3 Years Warranty

<b>ErP Waterproof Type</b>	 <b>B 20</b>	 <b>F 65</b>	 <b>R 67</b>
	Naked Strip	Silicone Tube	Silicone Extrusion
	3 Years Warranty	3 Years Warranty	3 Years Warranty

**WW-FLS102T23W-S120X-24(WCP)-HR-LD**

**Parameters for non-Erp**

IP Grade	Model NO.	CRI (Ra)	Rf	Rg	Typical Power (W/M)	Max. Power (W/M)	Color	LED Color Temp.(K) Wavelength(nm)*	3SDCM LED Color Temp.(K) Wavelength(nm)**	Typ. Luminous Flux LM/M(39.37in)	Rated voltage
<b>B 20</b>	WW-FLS102T23W-S120B-24(WCP)-HR-LD	80	82	96	9.44	10.38	Warm White	2600-2900K	/	510	DC 24V
							Standard White	5700-6500K	/	595	
<b>F 65</b>	WW-FLS102T23W-S120F-24(WCP)-HR-LD	80	82	96	9.44	10.38	Warm White	2600-2900K	/	500	DC 24V
							Standard White	5700-6500K	/	575	
<b>R 67</b>	WW-FLS102T23W-S120R-24(WCP)-HR-LD	80	82	96	9.44	10.38	Warm White	2600-2900K	/	500	DC 24V
							Standard White	5700-6500K	/	575	

Remarks:

- \*The above color temperature is the color temperature of LED source.
- The typ. Luminous flux tolerance range is  $\pm 10\%$  (subject to the manufacturer's instrument test).

Test condition of above technical data:

- Surrounding temperature: 26°C.
- Test while turning on.

WW-FLS102T23W-S120X-24(WCP)-HR-EP-LD

**Parameters for Erp**

IP Grade	Model NO.	CRI (Ra)	Rf	Rg	Typical Power (W/M)	Max. Power (W/M)	Color	LED Color Temp.(K) Wavelength(nm)*	Luminous Flux LM/M(39.37')	Lumen/watt	Energy Efficiency class	Rated voltage
E 20	WW-FLS102T23W-S120B-24(WCP)-HR-EP-LD	80	82	96	4.80	5.28	Warm White	2600-2900K	524	109	F	DC 24V
					4.80	5.28	Standard White	5700-6500K	610	127	E	
F 65	WW-FLS102T23W-S120F-24(WCP)-HR-EP-LD	80	82	96	4.80	5.28	Warm White	2600-2900K	512	107	F	DC 24V
					4.80	5.28	Standard White	5700-6500K	588	123	E	
R 67	WW-FLS102T23W-S120R-24(WCP)-HR-EP-LD	80	82	96	4.80	5.28	Warm White	2600-2900K	512	107	F	DC 24V
					4.80	5.28	Standard White	5700-6500K	588	123	E	

Remarks:

- \*The above color temperature is the color temperature of LED source.


Test condition of above technical data:

- Surrounding temperature: 26 °C.
- Test after 10 mins turned on.


ErP Note:

- According to the new ErP 2019/2020 regulation for each 0.5m or nearest 0.5m strip, the following requirements must be met:
- Measured power  $\leq$  Pon +5% ;
- Measured lumen  $\geq$  Useful luminous flux -10%;
- Measured CRI  $\geq$  Declared CRI-2
- The above technical data, including typical power are based on the test of 0.5m.

### Optical Test Diagram



### Dimension Drawing




IP Grade	A Cable Length	B cable diameter	C Strip length	D Strip width	E Strip thickness	F Front cap length	G End cap length	H Cap width	I Cap thickness
E20	300±10mm	Φ4.0±0.2mm	5000±50mm	10±0.5mm	1.2±0.5mm	/	/	/	/
	11.81±0.39in	0.16±0.01in	196.85±1.97in	0.39±0.02in	0.047±0.02in	/	/	/	/
E65	300±10mm	Φ4.0±0.2mm	5020±50mm	12±0.5mm	4.5±0.5mm	30±0.5mm	10±0.5mm	14.0±0.5mm	7.0±0.5mm
	11.81±0.39in	0.16±0.01in	197.64±1.97in	0.47±0.02in	0.19±0.02in	1.18±0.02in	0.39±0.02in	0.551±0.02in	0.28±0.02in
R67	300±10mm	Φ6.0±0.2mm	5020±50mm	12±0.5mm	5±0.5mm	30±0.5mm	10±0.5mm	14.0±0.5mm	7.0±0.5mm
	11.81±0.39in	0.25±0.008 in	197.64±1.97in	0.47±0.02in	0.20±0.02in	1.18±0.02in	0.39±0.02in	0.551±0.02in	0.28±0.02in

**Remarks:**

- If you need further information, please contact our sales manager.

## Circuit Diagram




## Standard Accessories

IP Grade	Category	Description	Picture	Part No.	Application
B 20	/	/	/	/	/
F 65	Connection Accessories	Front cap+End cap+Cable		WW-FLS102R-CW (12mm)	10mm Type F
	Installation Accessories	Installation Buckle+Screws		WW-FLS102JJA-MC	Waterproof strip
R 67	Connection Accessories	Front cap+End cap+Cable		WW-FLS102R-CW (12mm)	10mm Type R
	Installation Accessories	Installation Buckle+Screws		WW-FLS102JJA-MC	Waterproof strip

## Optional Accessories

IP Level	Category	Description	Picture	Part No.	Density
E 20	Strip to Strip	10 mm wide RGB light with connector		WW-FLS103B-2DD4(10MM)	≤84LEDs/M
	Strip to wire Connector	15cm long and 10 mm wide RGB lamp with single end connecting wire		WW-FLS103B-2FS4(10MM)	≤84LEDs/M
	Strip to Strip	15cm length and 10 mm board width RGB lamp with connecting wires at both ends		WW-FLS103B-2FD4(10MM)	≤84LEDs/M

## Packaging Diagram













## Packaging information

















IP Grade	Bag size	Inner carton		Outer carton		N.W	G.W	Outer carton volume
		Size	Reel/ctn	Size	Reel/ctn			
<b>B 20</b>	220*250*0.14mm	/	/	440*400 *260mm	52	3.80KG±10%	6.33KG±10%	0.04576 m3
	8.66*9.84*0.0056 in	/	/	17.32*15.748 *10.236 in	52	8.37Lbs±10%	13.88Lbs±10%	1.616 ft3
<b>F 65</b>	250*270*0.14mm	/	/	440*400 *260mm	40	8.20 KG±10%	14.08 KG±10%	0.04576m3
	9.84*10.63*0.0056 in	/	/	17.32*15.748 *10.236 in	40	18.07Lbs±10%	31.04 KG±10%	1.616 ft3
<b>R 67</b>	270*300*0.14mm	/	/	520*370*300mm	36	10.26 KG±10%	15.78 KG±10%	0.05772m3
	10.63*11.81*0.0055 in	/	/	20.47*14.57*11.81in	36	22.61Lbs±10%	34.78 KG±10%	2.14ft3


**Remarks :**


- Please contact our sales manager for customized package (color box, blister etc.)


 **Cautions**

IP20	IP54	IP65	IP67	IP68
				
Do not press the surface of LED	Pay attention to high temperature environment	Do not use in strong water waves environment	Resist strong water waves impact	Can apply to underwater do not deeper than 1m
				
Pay attention to damp-proof and dustproof	Do not apply to rainy environment	Can be applied to rainy environment	Do not apply to underwater environment for a long time	No direct sunlight

							
Do not tie a knot	Do not winding	Do not twist	Do not cut when it is working	Recommended the continuous working time do not exceed 12 hours daily	-20°C~+45°C (-4°F~+113°F)	0°C~+60°C (32°F~+140°F)	Operated by professionals
							
Pay attention to the application environment	IP Level will change after cutting	Do not pull and crash	Connected to power supply every 5 meters	Power supply must be connected to ground(GND)	The minimum bending diameter > 60mm	Power supply retain > 20%	Note the positive and negative poles

 For cutting LED strip operation, it is necessary to use the standard accessories provided by Dilux (e.g. DC wire, end-cap, front-cap, adhesive, etc.), and according to the correct cutting and connecting method for the installation.

 For avoiding LED get vulcanized, LED strip should be installed in the environment where does not has oil and corrosive substances. Such as these substances which contain Sulphur, Bromine, Iodine and Chlorine. Some other chemical elements which will cause Aromatic hydrocarbons releasing(such as: methylbenzene, xylene, methyl acetoacetate Ethyl acetate etc.),The environment in which includes strong acid and strong base.

 During the warranty period, only defective products are acceptable to be replaced by the factory. Factory is not responsible for other expenses because of replacement, such as transportation fee, installation fee, etc..

**\*\* If you do not follow the above "Cautions" to operate and result in damaging the product, the factory will not accept maintenance and return.**  
**\*\*The right of final interpretation is owned by Dilux.**